












## Alppila Tilt IP44 GU10 GLC RST Tilt

Alppila Tilt Outdoors wall luminaire No dim; IP44; IK03; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing st; Colour st; Cover Glass transparent

IP44 GU10 GLC RST Tilt				
PRODUCT CODE	CODE	KG	PRODUCT FAMILY	
4107268	A1ALAC	0.614	Alppila Tilt	







## IP44 GU10 GLC RST Tilt

EC002892

Mounting	
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	No
Suitable for recessed mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP44
Impact strength	IK03
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Suitable for emergency lighting	No
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm²)	2.5
Connection type	Screwed terminal

Structure	
Lamp type	LED exchan- geable
With lamp	No
Suitable for number of lamps	1
Lamp holder	GU10
Housing material	Stainless steel
Housing surface protection	Untreated
Housing colour	Stainless steel
Cover material	Glass transpa- rent
Type of grid	None
Control gear included	No
Exchangeable control gear	No
Energy efficiency class of light source according to EU regulation 2019/2015	Not required
Emergency power supply integrated	No
With air slots	No
Filament test according to IEC 60695-2-11	650 °C - 30 s

Dimming 1-10 V	10 10
3	
Dii DALL 2	lo .
Dimming DALI-2	
Dimming DALI	٧o
Dimming DMX	٧o
Dimming DSI N	١o
Dimming potentiometer (integrated)	٧o
Dimming LineSwitch	١o
Dimming manufacturer's proprietary system N	Vo.
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	Vo.
Dimming programmable N	Vo.
Dimming RF N	Vo.
Dimming Sine Wave Reduction	Vo.
Dimming Touch and Dim	Vo.
Dimming Zigbee	Vo.
Dimming with push-button	Vo.
No dimming function Y	es
With movement sensor	Vo.
With light sensor	Vo.
Constant luminous flux control	Vo.
Bluetooth operated	Vo.
Compatible with Apple HomeKit	Vo.
Compatible with Google Assistant	10
Compatible with Amazon Alexa	Vo.
IFTTT support available	10

Photometric data	
Light distributor	None
Light sharing	Symmetric
Light outlet	Direct
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	-20
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	25

Measurements	
Width (mm)	60
Height/depth (mm)	115
Length (mm)	60
Outer diameter (mm)	60

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Type of control gear	Not required
Protection class	I
Suitable for lamp power (min) (W)	1
Suitable for lamp power (max) (W)	7