



—O
3 x 2,5

IP44



Haaga

IP44 E27 PCO RST

Wall luminaire

The surface-mounted Haaga wall luminaire serves as a general light fixture as well as the number light on the side your building. The sleek design helps the lamp fit into its surroundings perfectly. The house number can be attached to the luminaire with the included black number stickers (3 x 0-9). The owner of a property is responsible for having an address number sign that can be seen from the street even in the dark in case an ambulance might need to see it, for example. For the light source, we recommend a LED bulb with an E27 base.

Haaga Universal luminaire No dim; IP44; Protection cl. II; LED exchangeable; Ending; 3x2.5mm²; Housing st; Colour st; Cover Plastic, opal; Number stickers 3 x 0-9 incl.



IP44 E27 PCO RST

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4107293	A1ULFB	0.62	Haaga

Mounting	
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	No
Suitable for recessed mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP44
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Suitable for emergency lighting	No
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm ²)	2.5
Connection type	Screwed terminal
Structure	
Lamp type	LED exchangeable
Light source included	No
Suitable for number of lamps	1
Lamp holder	E27
Housing material	Stainless steel
Housing surface protection	Untreated
Housing colour	Stainless steel
Cover material	Plastic, opal
Type of grid	None
Control gear included	No
Exchangeable control gear	No
Emergency power supply integrated	No
With air slots	No
Filament test according to IEC 60695-2-11	650 °C - 30 s
Dimming and control	
Dimmable	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With movement sensor	No
With light sensor	No
Constant luminous flux control	No
Bluetooth operated	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light distributor	Diffuser lens/optic/panel
Light sharing	Symmetric
Beam angle	Open beam
Light outlet	Direct
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated ambient temperature acc. IEC62722-2-1 (min) [°C]	-20
Rated ambient temperature acc. IEC62722-2-1 (max) [°C]	25

Measurements	
Width (mm)	310
Height/depth (mm)	165
Length (mm)	100

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Type of control gear	Not required
Protection class according to IEC 61140	II
Suitable for lamp power (min) (W)	1
Suitable for lamp power (max) (W)	11