



-O
3 x 2,5

IP44




Arvika

Arvika IP44 E27 white

Wall luminaire

The traditional Arvika wall luminaire with its smooth steel body and large glass dome is brimming with nostalgia and brings to mind the yards of old. The Arvika is ideal for lighting facades, outdoor entrances and corridors. The model can be combined with the bollard and wall luminaires in the Kartano series. The bulb is very visible inside the Arvika lamp, which means that you can significantly affect the mood and luminosity by choosing the right bulb.

Arvika Outdoors wall luminaire No dim; IP44;
Protection cl. I; LED exchangeable; Ending; 3x2.5mm²;
Housing st; Colour wh; Cover Glass transparent



Arvika IP44 E27 white

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4107297	A1ARAA	1.372	Arvika

Arvika IP44 E27 white

EC002892

Mounting	
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	No
Suitable for recessed mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Suitable for clamp-mounting	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP44
Degree of protection (IP), rear side	IP44
Degree of protection (IP), front side	IP44
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Suitable for emergency lighting	No
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm ²)	2.5
Structure	
With mounting material	Yes
Lamp type	LED exchangeable
Light source included	No
Suitable for number of lamps	1
Lamp holder	E27
Housing material	Steel
Housing surface protection	Plastic-coated
Housing colour	White
Cover material	Glass transparent
Energy efficiency class of light source according to EU regulation 2019/2015	Not required
Emergency power supply integrated	No
With switch	No
Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With movement sensor	No
With light sensor	No
Bluetooth operated	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light outlet	Direct
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated ambient temperature acc. IEC62722-2-1 (min) [°C]	-20
Rated ambient temperature acc. IEC62722-2-1 (max) [°C]	35

Measurements	
Width (mm)	370
Height/depth (mm)	303
Length (mm)	370

Electrotechnical data	
Nominal voltage (min) (V)	230
Nominal voltage (max) (V)	230
Type of control gear	Not required
Protection class according to IEC 61140	I