



-O
3 x 2,5

IP44




Park

IP44 E27 PCC GR

Wall luminaire

The clean-lined and stylish Park garden luminaires blend in with modern residential architecture. The steel rings inside the diffuser prevent glare and bring the modern design to life. Combine these models with Park Bollard luminaires to create a harmonious and stylish lighting solution for your outdoor spaces. You can change the atmosphere and level of illumination through the choice of lamp.

Park Outdoors wall luminaire No dim; IP44; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing st; Colour gr; Cover Plastic, transparent



IP44 E27 PCC GR

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4116103	A1PUBA	0.844	Park

Mounting	
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	No
Suitable for recessed mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Suitable for clamp-mounting	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP44
Degree of protection (IP), rear side	IP44
Degree of protection (IP), front side	IP44
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Suitable for emergency lighting	No
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm ²)	2.5
Connection type	Screwed terminal

Structure	
With mounting material	Yes
Lamp type	LED exchangeable
Light source included	No
Suitable for number of lamps	1
Lamp holder	E27
Housing material	Stainless steel
Housing surface protection	Powder coating
Housing colour	Grey
Cover material	Plastic, transparent
Type of grid	Other
Control gear included	No
Energy efficiency class of light source according to EU regulation 2019/2015	Not required
Emergency power supply integrated	No
With switch	No
With air slots	No
Filament test according to IEC 60695-2-11	650 °C - 30 s

Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With movement sensor	No
With light sensor	No
Constant luminous flux control	No
Bluetooth operated	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light distributor	Reflector
Light sharing	Symmetric
Light outlet	Direct
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated ambient temperature acc. IEC62722-2-1 (min) [°C]	-20
Rated ambient temperature acc. IEC62722-2-1 (max) [°C]	25

Measurements	
Width (mm)	115
Height/depth (mm)	280
Length (mm)	150
Outer diameter (mm)	100

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) [V]	230
Nominal voltage (max) [V]	230
Type of control gear	Not required
Protection class according to IEC 61140	I
Suitable for lamp power (min) [W]	1
Suitable for lamp power (max) [W]	10.5