



-O-  
3 x 2,5

IP44



# Park Bollard

## IP44 E27 PCC GR H920

Bollard luminaire

The clean-lined Park Bollard luminaires are designed for gardens and access routes. The steel rings inside the diffuser prevent glare and bring the modern design to life. You can create a harmonious entity by combining the bollard-mounted models with Park Wall luminaires. You can change the atmosphere and level of illumination through the choice of lamp. You can install the luminaires using a concrete base and ground mounting tube (4107058) or alternatively you can use a ground mounting tube (4107104) that can be installed without a separate base.

Park Bollard Outdoor luminaire IP44; Protection cl. I; LED exchangeable; Suitable for through wiring; 3x2.5mm<sup>2</sup>; Housing st; Colour gr; Cover Plastic, transparent



IP44 E27 PCC GR H920

| PRODUCT CODE | CODE   | KG    | PRODUCT FAMILY |
|--------------|--------|-------|----------------|
| 4116104      | A1PUBB | 1.758 | Park Bollard   |

IP44 E27 PCC GR H920

EC000301

| Mounting                                   |                             |
|--|-----------------------------|
| Type of luminaire                          | Bollard luminaire           |
| Degree of protection (IP)                  | IP44                        |
| Type of wiring                             | Suitable for through wiring |
| Number of poles                            | 3                           |
| Conductor cross section (mm <sup>2</sup> ) | 2.5                         |
| Connection type                            | Screwed terminal            |

| Structure  |                      |
|--|----------------------|
| With base plate  | No                   |
| Lamp type  | LED exchangeable     |
| Light source included  | No                   |
| Suitable for number of lamps   | 1                    |
| Lamp holder  | E27                  |
| Housing material   | Stainless steel      |
| Material quality housing material  | Stainless steel 304  |
| Surface protection   | Powder coating       |
| Housing colour   | Grey                 |
| Cover material   | Plastic, transparent |
| Control gear included  | No                   |
| Energy efficiency class of light source according to EU regulation 2019/2015 | Not required         |

| Dimming and control              |    |
|----------------------------------|----|
| With light sensor                | No |
| With movement sensor             | No |
| Constant luminous flux control   | No |
| Compatible with Apple HomeKit    | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa     | No |
| IFTTT support available          | No |

| Photometric data              |           |
|-------------------------------|-----------|
| Light distributor             | Reflector |
| Light sharing                 | Symmetric |
| Light outlet                  | Direct    |
| Colour temperature switchable | No        |
| Lumen setting adjustable      | No        |
| Beam angle adjustable         | No        |

#### Lifetime and capacity

| Measurements      |     |
|-------------------|-----|
| Width (mm)        | 160 |
| Height/depth (mm) | 920 |
| Length (mm)       | 100 |
| Diameter (mm)     | 100 |

| Electrotechnical data                   |              |
|---|--------------|
| Voltage type                            | AC           |
| Nominal voltage (min) (V)               | 220          |
| Nominal voltage (max) (V)               | 240          |
| Type of control gear                    | Not required |
| Protection class according to IEC 61140 | I            |
| Suitable for lamp power (min) (W)       | 1            |
| Suitable for lamp power (max) (W)       | 10.5         |