




PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4116186	T1WLAA	1.122	



Mounting	
Suitable for surface mounting	No
Suitable for recessed mounting	No
Suitable for wall mounting	No
Suitable for suspended mounting	Yes
Suitable for ceiling mounting	No
Suitable for traverse mounting	No
Suitable for pedestal/floor mounting	No
Suitable for light-track mounting	No
Suitable for clamp-mounting	No
Suitable for low voltage cable system	No
Degree of protection (IP)	IP54
Type of wiring	Ending
Fit for workplace acc. EN 12464-1	No

Structure	
Adjustability	Not adjustable
Lamp type	LED exchan-geable
With lamp	No
Suitable for number of lamps	1
Lamp holder	E27
Housing material	Plastic
Housing colour	Black
Cover material	Glass transpa-rent
Surface brushed	No
Control gear included	No
Exchangeable control gear	No
Emergency power supply integrated	No

Dimming and control	
With movement sensor	No
With light sensor	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI-2	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
IFTTT support available	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No

Photometric data	
Light sharing	Symmetric
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity

Measurements	
Width (mm)	130
Height/depth (mm)	400
Outer diameter (mm)	130

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Type of control gear	Not required
Protection class	II
Suitable for lamp power (min) (W)	1
Suitable for lamp power (max) (W)	60