



Reine Sensor



IP44 LED 9W/830 1200lm ANT

Reine Sensor Outdoors wall luminaire 9W 3000K 1200lm No dim; IP44; SL I; L70B50 30000h; LED not exchangeable; CRI>80; Ending; 3x2.5mm²; Housing al; Colour ant; Cover Plastic, opal; With light sensor; Letter and number stickers (A-J / 0-9) incl.



IP44 LED 9W/830 1200lm ANT

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4146709	A7GAMJ	0.65	Reine Sensor



Mounting	
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	No
Suitable for recessed mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP44
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Suitable for emergency lighting	No
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm ²)	2.5
Connection type	Screwed terminal

Structure	
Lamp type	LED not exchangeable
With lamp	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Aluminium
Housing surface protection	Powder coating
Housing colour	Anthracite
Cover material	Plastic, opal
Energy efficiency class of light source according to EU regulation 2019/2015	E
Emergency power supply integrated	No

Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With movement sensor	No
With light sensor	Yes
Constant luminous flux control	No
Bluetooth operated	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light sharing	Symmetric
Light outlet	Direct
Colour of light (alphanumeric)	White
Effective luminous flux (lm)	1200
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Colour rendering index CRI	80-89
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	30000
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	-20
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	35

Measurements	
Width (mm)	161
Height/depth (mm)	211
Length (mm)	59

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Protection class according to IEC 61140	I
Suitable for lamp power (min) (W)	9
Suitable for lamp power (max) (W)	9
Maximum system power (W)	9
Luminaire efficacy (lm/W)	133