




Näsby Double

IP54 14W/830 ANT

Wall luminaire

The compact Näsby Double LED wall luminaire suits many architectural styles. The Näsby's light beams point both up and down, which allows you to highlight the wall surfaces and structures of your building's facade, for example. The fixture is also suitable for indoor spaces such as staircases and hallways. You can quickly change the look by adjusting the width of the light beams. The manually adjustable beam limiters have a range of 0–80°. Colour temperature of either 3,000 K or 4,000 K.

Näsby Double Outdoors wall luminaire 14W 3000K
860lm No dim; IP54; Protection cl. I; L70B50 30000h;
LED not exchangeable; CRI>80; Suitable for through wiring; 3x2.5mm²; Housing al; Colour ant; Cover Plastic, transparent



| IP54 14W/830 ANT | | | |
|------------------|--------|------|----------------|
| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
| 4508601 | A1NBAF | 0.97 | Näsby Double |



| Mounting | |
|--|------------------------------|
| Suitable for wall mounting | Yes |
| Suitable for suspended mounting | No |
| Suitable for ceiling mounting | No |
| Suitable for recessed mounting | No |
| Suitable for surface mounting | Yes |
| Suitable for light line configuration | No |
| Fit for workplace acc. EN 12464-1 | No |
| Degree of protection (IP) | IP54 |
| Degree of protection (IP), rear side | Other |
| Degree of protection (IP), front side | IP54 |
| Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24 | No |
| Suitable for emergency lighting | No |
| Type of wiring | Suitable for thorough wiring |
| Number of poles | 3 |
| Conductor cross section (mm ²) | 2.5 |
| Connection type | Screwless terminal |
| Structure | |
| Lamp type | LED not exchangeable |
| Light source included | Yes |
| Suitable for number of lamps | 2 |
| Lamp holder | Other |
| Housing material | Aluminium |
| Housing surface protection | Powder coating |
| Housing colour | Anthracite |
| Cover material | Plastic, transparent |
| Type of grid | None |
| Control gear included | Yes |
| Exchangeable control gear | Yes |
| Energy efficiency class of light source according to EU regulation 2019/2015 | F |
| Emergency power supply integrated | No |
| With air slots | No |

| Dimming and control | |
|--|-----------------------|
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI | No |
| Dimming DALI-2 | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming LineSwitch | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming trailing edge | No |
| Dimming leading edge | No |
| Dimming programmable | No |
| Dimming potentiometer (integrated) | No |
| Dimming RF | No |
| Dimming Sine Wave Reduction | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| No dimming function | Yes |
| With movement sensor | No |
| With light sensor | No |
| Constant luminous flux control | No |
| Bluetooth operated | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |
| Photometric data | |
| Light distributor | Reflector |
| Light sharing | Symmetric |
| Beam angle | Variable |
| Light outlet | Direct/indirect |
| Colour of light (alphanumeric) | White |
| Effective luminous flux (lm) | 860 |
| Colour temperature (min) (K) | 3000 |
| Colour temperature (max) (K) | 3000 |
| Colour rendering index (CRI/Ra) | 80-89 |
| Colour temperature switchable | No |
| Lumen setting adjustable | No |
| Beam angle adjustable | Continuously variable |
| Lifetime and capacity | |
| Rated life time L70/B50 at 25 °C (h) | 30000 |
| Rated ambient temperature acc. IEC62722-2-1 (min) (°C) | -20 |
| Rated ambient temperature acc. IEC62722-2-1 (max) (°C) | 25 |
| Measurements | |
| Width (mm) | 94 |
| Height/depth (mm) | 138 |
| Length (mm) | 137 |

| Electrotechnical data | |
|---|---|
| Voltage type | AC |
| Nominal voltage (min) (V) | 220 |
| Nominal voltage (max) (V) | 240 |
| Nominal current (min) (mA) | 300 |
| Nominal current (max) (mA) | 300 |
| Type of control gear | LED operating device current-controlled |
| Protection class according to IEC 61140 | I |
| Suitable for lamp power (min) (W) | 14 |
| Suitable for lamp power (max) (W) | 14 |
| Maximum system power (W) | 14 |
| Luminaire efficacy (lm/W) | 61 |
| Power factor | 0.8 |