



-O-
3 x 2,5

IP54




Näsby Double

IP54 14W/840 ANT

Wall luminaire

The compact Näsby Double LED wall luminaire suits many architectural styles. The Näsby's light beams point both up and down, which allows you to highlight the wall surfaces and structures of your building's facade, for example. The fixture is also suitable for indoor spaces such as staircases and hallways. You can quickly change the look by adjusting the width of the light beams. The manually adjustable beam limiters have a range of 0–80°. Colour temperature of either 3,000 K or 4,000 K.

Näsby Double Outdoors wall luminaire 14W 4000K
860lm No dim; IP54; Protection cl. I; L70B50 30000h;
LED not exchangeable; CRI>80; Suitable for through wiring; 3x2.5mm²; Housing al; Colour ant; Cover Plastic, transparent



IP54 14W/840 ANT

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4508603	A1NBAH	0.97	Näsby Double



Mounting	
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	No
Suitable for recessed mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP54
Degree of protection (IP), rear side	Other
Degree of protection (IP), front side	IP54
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Suitable for emergency lighting	No
Type of wiring	Suitable for thorough wiring
Number of poles	3
Conductor cross section (mm ²)	2.5
Connection type	Screwless terminal
Structure	
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	2
Lamp holder	Other
Housing material	Aluminium
Housing surface protection	Powder coating
Housing colour	Anthracite
Cover material	Plastic, transparent
Type of grid	None
Control gear included	Yes
Exchangeable control gear	Yes
Energy efficiency class of light source according to EU regulation 2019/2015	F
Emergency power supply integrated	No
With air slots	No

Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With movement sensor	No
With light sensor	No
Constant luminous flux control	No
Bluetooth operated	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Photometric data	
Light distributor	Reflector
Light sharing	Symmetric
Beam angle	Variable
Light outlet	Direct/indirect
Colour of light (alphanumeric)	White
Effective luminous flux (lm)	860
Colour temperature (min) (K)	4000
Colour temperature (max) (K)	4000
Colour rendering index (CRI/Ra)	80-89
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	Continuously variable
Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	30000
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	-20
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	25
Measurements	
Width (mm)	94
Height/depth (mm)	138
Length (mm)	137

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	300
Nominal current (max) (mA)	300
Type of control gear	LED operating device current-controlled
Protection class according to IEC 61140	I
Suitable for lamp power (min) (W)	14
Suitable for lamp power (max) (W)	14
Maximum system power (W)	14
Luminaire efficacy (lm/W)	61
Power factor	0.8