



-O-
3 x 2,5

IP65

IK03






Holm

IP65 GU10 GLFR RST

Holm Ground luminaire max. 7W No dim; IP65; IK03; Protection cl. I; LED exchangeable; Suitable for through wiring; 3x2.5mm²; Colour st; Cover Glass matt/satinized

IP65 GU10 GLFR RST

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4510237	A5TEVA	0.582	Holm



Mounting	
Degree of protection (IP)	IP65
Impact strength	IK03
Over rollable	No
Max. surface temperature [°C]	59
Type of wiring	Suitable for through wiring
Number of poles	3
Conductor cross section (mm ²)	2.5
Connection type	Screwed terminal
Electrical connection with connector system	No

Structure	
Lamp type	LED exchangeable
Light source included	No
Suitable for number of lamps	1
Lamp holder	GU10
Housing material	Aluminium
Housing colour	Stainless steel
Cover material	Glass matt/satinized
Control gear included	No
Exchangeable control gear	No
Adjustable	No
Energy efficiency class of light source according to EU regulation 2019/2015	Not required

Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming mains voltage modulation	No
Dimming manufacturer's proprietary system	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming potentiometer (integrated)	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming with push-button	No
Dimming Zigbee	No
No dimming function	Yes
Constant luminous flux control	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light distributor	Diffuser lens/optic/panel
Light sharing	Symmetric
Beam angle	Open beam
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity

Measurements	
Width (mm)	119
Height/depth (mm)	155
Length (mm)	119
Outer diameter (mm)	119
Built-in width (mm)	100
Built-in height/depth (mm)	155
Built-in length (mm)	100

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Type of control gear	Not required
Protection class according to IEC 61140	I
Suitable for lamp power (min) (W)	1
Suitable for lamp power (max) (W)	7