

# Onni

## 4W 15000h BX

For all residential lighting needs

An extensive lamp range offering solutions for all home lighting needs. Lightweight and durable lamps fully replace incandescent, halogen and energy-saving lamps. The lamps feature a pleasant warm white colour temperature (2700 K). The opal light source provides glare-free illumination. Technical specifications are clearly presented. Ensure compatibility between the range's 12 V lamps and the transformer.



| 4W 15000h BX |        |       |                |
|--------------|--------|-------|----------------|
| PRODUCT CODE | CODE   | KG    | PRODUCT FAMILY |
| 4710232      | A7ONNG | 0.021 | Onni           |

## 4W 15000h BX

EC001959

### Mounting

|                           |      |
|---------------------------|------|
| Degree of protection (IP) | IP20 |
|---------------------------|------|

### Structure

|                |       |
|----------------|-------|
| Colour         | White |
| Housing colour | White |

### Dimming and control

|                                  |     |
|----------------------------------|-----|
| Dimmable                         | No  |
| Dimming Touch and Dim            | No  |
| Dimming Zigbee                   | No  |
| Dimming Bluetooth                | No  |
| Dimming Wi-Fi                    | No  |
| No dimming function              | Yes |
| Remote operation possible        | No  |
| With movement sensor             | No  |
| With remote control              | No  |
| With twilight switch             | No  |
| Compatible with Apple HomeKit    | No  |
| Compatible with Google Assistant | No  |
| Compatible with Amazon Alexa     | No  |
| IFTTT support available          | No  |

### Photometric data

|                                     |              |
|-------------------------------------|--------------|
| Luminous flux (min) (lm)            | 470          |
| Luminous flux (max) (lm)            | 470          |
| Colour rendering index (CRI/Ra)     | 80-89        |
| Colour of light acc. EN 12464-1     | Warm <3300 K |
| Colour temperature (min) (K)        | 2700         |
| Colour temperature (max) (K)        | 2700         |
| Beam angle (min) (°)                | 360          |
| Beam angle (max) (°)                | 360          |
| Colour consistency (McAdam ellipse) | SDCM6        |

### Lifetime and capacity

### Measurements

|               |    |
|---------------|----|
| Diameter (mm) | 35 |
| Length (mm)   | 97 |

### Electrotechnical data

|                           |     |
|---------------------------|-----|
| Nominal voltage (min) (V) | 220 |
| Nominal voltage (max) (V) | 240 |
| Power factor              | 0.5 |
| Lamp power (min) (W)      | 4   |
| Lamp power (max) (W)      | 4   |
| Voltage type              | AC  |