

Oiva

2.7W 15000h BX

Pure white light

The Oiva lamp range with white light (3000 K) covers the most common lighting needs in the home. The opal light source provides glare-free illumination. Replace your old lamps with long-lasting and energy-efficient LED lamps. The technical information is clearly presented on the packaging.

Opal P45 bulb LED lamp 2.7W 3000K E14 250lm 15000h 45x78mm, cardboard packing. Supply frequency ~50/60Hz.



| 2.7W 15000h BX | | | |
|----------------|--------|------|----------------|
| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
| 4711482 | A70IAD | 0.02 | Oiva |

2.7W 15000h BX
EC001959

Mounting

| | |
|---------------------------|------|
| Degree of protection (IP) | IP20 |
|---------------------------|------|

Structure

| | |
|----------------|-------|
| Colour | White |
| Housing colour | White |

Dimming and control

| | |
|----------------------------------|-----|
| Dimmable | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming Bluetooth | No |
| Dimming Wi-Fi | No |
| No dimming function | Yes |
| Remote operation possible | No |
| With movement sensor | No |
| With remote control | No |
| With twilight switch | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

Photometric data

| | |
|--|--------------|
| Luminous flux (min) (lm) | 250 |
| Luminous flux (max) (lm) | 250 |
| Colour rendering index (CRI/Ra) | 80-89 |
| Colour of light acc. EN 12464-1 | Warm <3300 K |
| Colour temperature (min) (K) | 3000 |
| Colour temperature (max) (K) | 3000 |
| Beam angle (min) (°) | 240 |
| Beam angle (max) (°) | 240 |
| Colour consistency (McAdam ellipse) | SDCM6 |
| Photobiological safety according to EN 62471 | RG0 |

Lifetime and capacity

Measurements

| | |
|---------------|----|
| Diameter (mm) | 45 |
| Length (mm) | 78 |

Electrotechnical data

| | |
|-------------------------------|-------|
| Nominal voltage (min) (V) | 220 |
| Nominal voltage (max) (V) | 240 |
| Nominal current (min) (mA) | 28 |
| Nominal current (max) (mA) | 28 |
| Power factor | 0.5 |
| Lamp power (min) (W) | 2.7 |
| Lamp power (max) (W) | 2.7 |
| Voltage type | AC |
| Energy Efficiency Index (EEI) | 0.103 |