Decor FIL 4.5W 15000h BX

Decorative lamp, antique surface

The lamps in the Amber series are modern LED versions of decorative carbon filament lamps. Their light is warm and soft, and they offer excellent 360-degree light distribution. The cover has a warm amber hue. When combined with the elegant cord, the lamps look impressive even without a lampshade. The ecofriendly cardboard packages are colour-coded. The colour indicates the corresponding incandescent bulb, making the choice simpler for the consumer. Technical specifications are also clearly presented.

Clear classic filament LED lamp 4.5W 2200K E27 360lm 15000h 60x108mm, full glass, colour Amber, cardboard packing. Supply frequency ~50/60Hz.

| FIL 4.5W 15000h BX | | | | | |
|--------------------|--------|------|----------------|--|--|
| PRODUCT CODE | CODE | KG | PRODUCT FAMILY | | |
| 4711508 | A7ANAC | 0.04 | Decor | | |



FIL 4.5W 15000h BX

EC001959

| Mounting | |
|--|--------------|
| Degree of protection (IP) | Other |
| Structure | |
| Colour | Amber |
| Housing colour | Colourless |
| | |
| Dimming and control | |
| Dimming phase cut-off | No |
| Dimming phase cut-on | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming Bluetooth | No |
| Dimming Wi-Fi | No |
| No dimming function | Yes |
| Remote operation possible | No |
| With movement sensor | No |
| With remote control | No |
| With twilight switch | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |
| · · · · · · · | |
| Photometric data | |
| Luminous flux (min) (lm) | 360 |
| Luminous flux (max) (lm) | 360 |
| Colour rendering index CRI | 80-89 |
| Colour of light acc. EN 12464-1 | Warm <3300 K |
| Colour temperature (min) (K) | 2200 |
| Colour temperature (max) (K) | 2200 |
| Beam angle (min) | 360 |
| Beam angle (max) | 360 |
| Colour consistency (McAdam ellipse) | SDCM6 |
| Photobiological safety according to EN 62471 | RG1 |
| | |
| Lifetime and capacity | |
| Measurements | |
| Diameter (mm) | 60 |
| Length (mm) | 108 |
| • | |
| Electrotechnical data | |
| Nominal voltage (min) (V) | 220 |
| Nominal voltage (max) (V) | 240 |
| Nominal current (min) (mA) | 36 |
| Nominal current (max) (mA) | 36 |
| Power factor | 0.5 |
| Voltage type | AC |
| Energy Efficiency Index (EEI) | 0.131 |
| Total harmonic distortion | 170 |
| | |

