

# Decor

## FIL 4.5W 15000h BX

Dimmable decorative lamp with antique finish, warm light

The antique-finished LED decorative lamps in the Amber series create a distinctive and atmospheric ambience at home. Dimmability is indicated by the DIM symbol on the packaging. Use only an LED-compatible dimmer. The omnidirectional, amber-tinted glass bulb emits warm and soft light also towards the base. Combined with a stylish lamp cord, the lamps make a striking feature even without a lampshade. Technical specifications are clearly presented on the packaging.

Clear globe dimmable filament LED lamp 4.5W 2200K E27 360lm 15000h 125x178mm, full glass, colour Amber, cardboard packing. Supply frequency ~50/60Hz.



### FIL 4.5W 15000h BX

| PRODUCT CODE | CODE   | KG    | PRODUCT FAMILY |
|--------------|--------|-------|----------------|
| 4711592      | A7AKAM | 0.102 | Decor          |

**FIL 4.5W 15000h BX**

EC001959

| <b>Mounting</b>           |      |
|---------------------------|------|
| Degree of protection (IP) | IP20 |

  

| <b>Structure</b> |            |
|------------------|------------|
| Colour           | Amber      |
| Housing colour   | Colourless |

  

| <b>Dimming and control</b>       |     |
|----------------------------------|-----|
| Dimmable                         | Yes |
| Dimming trailing edge            | Yes |
| Dimming leading edge             | Yes |
| Dimming Touch and Dim            | No  |
| Dimming Zigbee                   | No  |
| Dimming Bluetooth                | No  |
| Dimming Wi-Fi                    | No  |
| No dimming function              | No  |
| Remote operation possible        | No  |
| With movement sensor             | No  |
| With remote control              | No  |
| With twilight switch             | No  |
| Compatible with Apple HomeKit    | No  |
| Compatible with Google Assistant | No  |
| Compatible with Amazon Alexa     | No  |
| IFTTT support available          | No  |

  

| <b>Photometric data</b>                      |              |
|--|--------------|
| Luminous flux (min) (lm)                     | 360          |
| Luminous flux (max) (lm)                     | 360          |
| Colour rendering index (CRI/Ra)              | 80-89        |
| Colour of light acc. EN 12464-1              | Warm <3300 K |
| Colour temperature (min) (K)                 | 2200         |
| Colour temperature (max) (K)                 | 2200         |
| Beam angle (min) (°)                         | 360          |
| Beam angle (max) (°)                         | 360          |
| Colour consistency (McAdam ellipse)          | SDCM6        |
| Photobiological safety according to EN 62471 | RG1          |

  

| <b>Lifetime and capacity</b> |  |
|------------------------------|--|
|------------------------------|--|

  

| <b>Measurements</b> |     |
|---------------------|-----|
| Diameter (mm)       | 125 |
| Length (mm)         | 178 |

  

| <b>Electrotechnical data</b>  |       |
|-------------------------------|-------|
| Nominal voltage (min) (V)     | 220   |
| Nominal voltage (max) (V)     | 240   |
| Nominal current (min) (mA)    | 26    |
| Nominal current (max) (mA)    | 26    |
| Power factor                  | 0.7   |
| Lamp power (min) (W)          | 4.5   |
| Lamp power (max) (W)          | 4.5   |
| Voltage type                  | AC    |
| Energy Efficiency Index (EEI) | 0.131 |
| Total harmonic distortion     | 100   |