Pro 4.2W 25000h BX

Lamp range for basic use - pure white

Airam's PRO LED 3000 K series covers all light source needs for basic use. This series includes the most common bulb types. The lamps are packed in cardboard boxes that clearly indicate the key technical specifications. Special characteristics for the lamps in this series include an extremely long operating life (25,000 h) and a high number of switch-on cycles (500,000). The colour temperature is pure white (3000 K).

Opal candle LED lamp 4.2W 3000K E14 470lm 25000h 35x102mm, cardboard packing. Supply frequency ~50/60Hz.

4.2W 25000h BX			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4713422	A7PRAH	0.03	Pro



AIRAM®





4.2W 25000h BX EC001959

Mounting	
Degree of protection (IP)	Other
Structure	
Colour	White
Housing colour	White
Dimming and control	
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Photometric data	
Luminous flux (min) (lm)	470
Luminous flux (max) (lm)	470
Colour rendering index CRI	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Beam angle (min)	280
Beam angle (max)	280
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG0
Lifetime and capacity	
Measurements	
Diameter (mm)	35
Length (mm)	102
-	
Electrotechnical data	
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	40
Nominal current (max) (mA)	40
Power factor	0.4
Voltage type	AC
Energy Efficiency Index (EEI)	0.1

