

Tubular

9.5W 15000h BX

Slim tubular bulb

The bulb of a Tubular LED lamp has a long, slim, cylindrical shape. The light output covers the entire surface of the lamp. Tubular lamps are especially suitable for luminaires where a standard bulb does not fit and/or where an even light distribution across the whole luminaire is desired. Technical specifications are clearly presented on the packaging. Available colour temperatures are warm white and cool white (2700 K and 4000 K).

Opal tubular LED lamp for outdoor lighting 9.5W 2700K E27 1055lm 15000h 45x152mm, cardboard packing. Supply frequency ~50/60Hz.



9.5W 15000h BX

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4713451	A7LEDG	0.086	Tubular

9.5W 15000h BX

EC001959

Mounting	
Degree of protection (IP)	IP20

Structure	
Colour	White
Housing colour	White

Dimming and control	
Dimmable	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Luminous flux (min) (lm)	1055
Luminous flux (max) (lm)	1055
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	2700
Colour temperature (max) (K)	2700
Beam angle (min) (°)	270
Beam angle (max) (°)	270
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

Lifetime and capacity	
-----------------------	--

Measurements	
Diameter (mm)	45
Length (mm)	152

Electrotechnical data	
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	72
Nominal current (max) (mA)	72
Power factor	0.5
Lamp power (min) (W)	9.5
Lamp power (max) (W)	9.5
Voltage type	AC
Energy Efficiency Index (EEI)	0.118