

## Airam Led

### 4.5W 15000h BX

#### LED filament

A range of clear-glass LED filament lamps. The beautiful filament lamps are particularly well suited for chandeliers or luminaires where the light source is clearly visible. The lamps feature a pleasant warm white colour temperature (2700 K). The technical information is clearly presented on the packaging.

Clear classic filament LED lamp 4.5W 2700K E27 470lm 15000h 60x108mm, cardboard packing. Supply frequency ~50/60Hz.



#### 4.5W 15000h BX

| PRODUCT CODE | CODE   | KG   | PRODUCT FAMILY |
|--------------|--------|------|----------------|
| 4713483      | A7GABD | 0.04 | Airam Led      |

## 4.5W 15000h BX

EC001959

### Mounting

|                           |      |
|---------------------------|------|
| Degree of protection (IP) | IP20 |
|---------------------------|------|

### Structure

|                |            |
|----------------|------------|
| Colour         | Other      |
| Housing colour | Colourless |

### Dimming and control

|                                  |     |
|----------------------------------|-----|
| Dimmable                         | No  |
| Dimming trailing edge            | No  |
| Dimming leading edge             | No  |
| Dimming Touch and Dim            | No  |
| Dimming Zigbee                   | No  |
| Dimming Bluetooth                | No  |
| Dimming Wi-Fi                    | No  |
| No dimming function              | Yes |
| Remote operation possible        | No  |
| With movement sensor             | No  |
| With remote control              | No  |
| With twilight switch             | No  |
| Compatible with Apple HomeKit    | No  |
| Compatible with Google Assistant | No  |
| Compatible with Amazon Alexa     | No  |
| IFTTT support available          | No  |

### Photometric data

|                                              |              |
|----------------------------------------------|--------------|
| Luminous flux (min) (lm)                     | 470          |
| Luminous flux (max) (lm)                     | 470          |
| Colour rendering index (CRI/Ra)              | 80-89        |
| Colour of light acc. EN 12464-1              | Warm <3300 K |
| Colour temperature (min) (K)                 | 2700         |
| Colour temperature (max) (K)                 | 2700         |
| Beam angle (min) (°)                         | 360          |
| Beam angle (max) (°)                         | 360          |
| Colour consistency (McAdam ellipse)          | SDCM6        |
| Photobiological safety according to EN 62471 | RG1          |

### Lifetime and capacity

### Measurements

|               |     |
|---------------|-----|
| Diameter (mm) | 60  |
| Length (mm)   | 108 |

### Electrotechnical data

|                               |       |
|-------------------------------|-------|
| Nominal voltage (min) (V)     | 220   |
| Nominal voltage (max) (V)     | 240   |
| Nominal current (min) (mA)    | 36    |
| Nominal current (max) (mA)    | 36    |
| Power factor                  | 0.4   |
| Lamp power (min) (W)          | 4.5   |
| Lamp power (max) (W)          | 4.5   |
| Voltage type                  | AC    |
| Energy Efficiency Index (EEI) | 0.107 |
| Total harmonic distortion     | 170   |