

Airam Led

2.5W 15000h BX

LED filament

The filament lamps with clear covers replace old, clear incandescent bulbs and halogen lamps. Thin LED strips are used to generate the light. Filament lamps are ideal for chandeliers. The colour temperature is a pleasant warm white (2700 K). The eco-friendly cardboard packages are colour-coded. The colour indicates the corresponding incandescent bulb, making the choice simpler for the consumer. Technical specifications are also clearly presented.

Clear globe filament LED lamp 2.5W 2700K E27 250lm 15000h 125x178mm, cardboard packing. Supply frequency ~50/60Hz.



| 2.5W 15000h BX | | | |
|----------------|--------|-----|----------------|
| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
| 4713487 | A7GABH | 0.1 | Airam Led |

2.5W 15000h BX

EC001959

Mounting

| | |
|---------------------------|-------|
| Degree of protection (IP) | Other |
|---------------------------|-------|

Structure

| | |
|----------------|------------|
| Colour | Other |
| Housing colour | Colourless |

Dimming and control

| | |
|----------------------------------|-----|
| Dimming phase cut-off | No |
| Dimming phase cut-on | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming Bluetooth | No |
| Dimming Wi-Fi | No |
| No dimming function | Yes |
| Remote operation possible | No |
| With movement sensor | No |
| With remote control | No |
| With twilight switch | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

Photometric data

| | |
|--|--------------|
| Luminous flux (min) (lm) | 250 |
| Luminous flux (max) (lm) | 250 |
| Colour rendering index CRI | 80-89 |
| Colour of light acc. EN 12464-1 | Warm <3300 K |
| Colour temperature (min) (K) | 2700 |
| Colour temperature (max) (K) | 2700 |
| Beam angle (min) | 360 |
| Beam angle (max) | 360 |
| Colour consistency (McAdam ellipse) | SDCM6 |
| Photobiological safety according to EN 62471 | RG1 |

Lifetime and capacity

Measurements

| | |
|---------------|-----|
| Diameter (mm) | 125 |
| Length (mm) | 178 |

Electrotechnical data

| | |
|-------------------------------|-------|
| Nominal voltage (min) (V) | 220 |
| Nominal voltage (max) (V) | 240 |
| Nominal current (min) (mA) | 19 |
| Nominal current (max) (mA) | 19 |
| Power factor | 0.4 |
| Voltage type | AC |
| Energy Efficiency Index (EEI) | 0.096 |
| Total harmonic distortion | 135 |