

## Decor

### FIL 4.5W 15000h BX

Dimmable decorative lamp with antique finish, warm light

The antique-finished LED decorative lamps in the Amber series create a distinctive and atmospheric ambience at home. Dimmability is indicated by the DIM symbol on the packaging. Use only an LED-compatible dimmer. The omnidirectional, amber-tinted glass bulb emits warm and soft light also towards the base. Combined with a stylish lamp cord, the lamps make a striking feature even without a lampshade. Technical specifications are clearly presented on the packaging.

Clear candle dimmable filament LED lamp 4.5W 2200K E14 360lm 15000h 35x97mm, full glass, colour Amber, cardboard packing. Supply frequency ~50/60Hz.



FIL 4.5W 15000h BX			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4713708	A7GACC	0.02	Decor

#### Mounting

Degree of protection (IP)	IP20
---------------------------	------

#### Structure

Colour	Amber
Housing colour	Colourless

#### Dimming and control

Dimmable	Yes
Dimming trailing edge	Yes
Dimming leading edge	Yes
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	No
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

#### Photometric data

Luminous flux (min) (lm)	360
Luminous flux (max) (lm)	360
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	2200
Colour temperature (max) (K)	2200
Beam angle (min) (°)	360
Beam angle (max) (°)	360
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

#### Lifetime and capacity

#### Measurements

Diameter (mm)	35
Length (mm)	97

#### Electrotechnical data

Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	26
Nominal current (max) (mA)	26
Power factor	0.7
Lamp power (min) (W)	4.5
Lamp power (max) (W)	4.5
Voltage type	AC
Energy Efficiency Index (EEI)	0.131
Total harmonic distortion	100