

## Airam Led

### 4.5W 880cd 15000h BL

For all residential lighting needs

An extensive lamp range offering solutions for all home lighting needs. Lightweight and durable lamps fully replace incandescent, halogen and energy-saving lamps. The lamps feature a pleasant warm white colour temperature (2700 K). The opal light source provides glare-free illumination. Technical specifications are clearly presented. Ensure compatibility between the range's 12 V lamps and the transformer.

Clear MR16 reflector LED lamp 12V 4.5W 2700K GU5.3 345lm 880cd 36D 15000h 50x45mm, full glass, blister packing. Supply frequency ~50/60Hz.



#### 4.5W 880cd 15000h BL

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4713813	A7GAFK	0.04	Airam Led

4.5W 880cd 15000h BL  
EC001959

#### Mounting

Degree of protection (IP)	IP20
---------------------------	------

#### Structure

Colour	Other
Housing colour	Colourless

#### Dimming and control

Dimmable	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

#### Photometric data

Luminous flux (min) (lm)	345
Luminous flux (max) (lm)	345
Luminous intensity (cd)	880
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	2700
Colour temperature (max) (K)	2700
Beam angle (min) (°)	36
Beam angle (max) (°)	36
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

#### Lifetime and capacity

#### Measurements

Diameter (mm)	50
Length (mm)	45

#### Electrotechnical data

Nominal voltage (min) (V)	12
Nominal voltage (max) (V)	12
Nominal current (min) (mA)	616
Nominal current (max) (mA)	616
Power factor	0.5
Lamp power (min) (W)	4.5
Lamp power (max) (W)	4.5
Voltage type	AC