SmartHome FIL 4.9W 15000h BX

These amber lamps make an eye-catching design element as they are.

Thanks to their beautiful design, the elegant Airam SmartHome Amber CCT LED lamps do not even require a lampshade. The LED filaments are spiralshaped and the bulb is amber in colour. You can use your mobile device to adjust the lamp's colour temperature from warm to white (1,800-3,000 K). If you switch off the lamp from the switch, the last lighting setting is saved in the system's memory. Airam's SmartHome products can be controlled with Airam's SmartHome app. Download the app from the App Store or the Google Play Store. The app is available in Finnish, Swedish and English. You can connect the devices to your Wi-Fi network. You do not need a separate hub! The products can be connected to the Google Assistant, Amazon Alexa an Siri Shortcut voice control systems.

SmartHome clear Edison bulb CCT WiFi filament LED lamp 4.9W 1800-3000K E27 350lm 15000h 64x142mm, colour Amber, cardboard packing. Supply frequency ~50/60Hz.

FIL 4.9W 15000h BX					
PRODUCT CODE	CODE	KG	PRODUCT FAMILY		
4713892	A7GAJ0	0.05	SmartHome		



FIL 4.9W 15000h BX

EC001959

Mounting	
Degree of protection (IP)	Other
begree or protection (ii)	Other
Structure	
Colour	Amher
Housing colour	Colourless
Trousing cotour	ootourte33
Dimming and control	
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	Yes
Remote operation possible	Yes
With movement sensor	No
With remote control	Yes
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	Yes
Compatible with Amazon Alexa	Yes
IFTTT support available	No
Photometric data	
Luminous flux (min) (lm)	350
Luminous flux (max) (lm)	350
Colour rendering index CRI	80-89
Colour temperature (min) (K)	1800
Colour temperature (max) (K)	3000
Beam angle (min)	320
Beam angle (max)	320
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1
Lifetime and capacity	
Measurements	
Diameter (mm)	64
Length (mm)	142
Fl	
Electrotechnical data	220
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	47
Nominal current (max) (mA)	47
Power factor	0.5
Voltage type	AC
Energy Efficiency Index (EEI)	0.146
Total harmonic distortion	135

