

SmartHome

FIL 4.9W 15000h BX

Beautiful decorative lamps

The elegant and decorative Airam SmartHome Amber CCT LED lamps are so visually striking that they do not necessarily require a lampshade. The LED filaments are shaped in a spiral design, and the glass has an antique-tinted finish. Easily adjust the colour temperature from very warm to warm white (1800–3000 K) using your mobile device. The lamps can also be switched on and off using a standard wall switch, while the last used lighting setting is stored in the lamp's memory. Airam SmartHome smart products are controlled via the Airam SmartHome app. Download the free app from the App Store or Google Play. Connect the devices directly to your home WiFi network – no separate hub is required. The products can also be connected to voice control via Google Assistant, Amazon Alexa or Siri Shortcuts.

SmartHome clear globe CCT WiFi filament LED lamp
4.9W 1800-3000K E27 350lm 15000h 125x172mm,
colour Amber, spiral filament, cardboard packing.
Supply frequency ~50/60Hz.



FIL 4.9W 15000h BX

| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
|--------------|--------|-------|----------------|
| 4713894 | A7GAJQ | 0.099 | SmartHome |

FIL 4.9W 15000h BX

EC001959

| Mounting | |
|---------------------------|------|
| Degree of protection (IP) | IP20 |

| Structure | |
|------------------|------------|
| Colour | Amber |
| Housing colour | Colourless |

| Dimming and control | |
|----------------------------------|-----|
| Dimming trailing edge | No |
| Dimming leading edge | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming Bluetooth | No |
| Dimming Wi-Fi | Yes |
| No dimming function | No |
| Remote operation possible | Yes |
| With movement sensor | No |
| With remote control | Yes |
| With twilight switch | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | Yes |
| Compatible with Amazon Alexa | Yes |
| IFTTT support available | No |

| Photometric data | |
|--|--------------|
| Luminous flux (min) (lm) | 350 |
| Luminous flux (max) (lm) | 350 |
| Colour rendering index (CRI/Ra) | 80-89 |
| Colour of light acc. EN 12464-1 | Warm <3300 K |
| Colour temperature (min) (K) | 1800 |
| Colour temperature (max) (K) | 3000 |
| Beam angle (min) (°) | 320 |
| Beam angle (max) (°) | 320 |
| Colour consistency (McAdam ellipse) | SDCM6 |
| Photobiological safety according to EN 62471 | RG1 |

| Lifetime and capacity | |
|------------------------------|--|
|------------------------------|--|

| Measurements | |
|---------------------|-----|
| Diameter (mm) | 125 |
| Length (mm) | 172 |

| Electrotechnical data | |
|-------------------------------|-------|
| Nominal voltage (min) (V) | 220 |
| Nominal voltage (max) (V) | 240 |
| Nominal current (min) (mA) | 47 |
| Nominal current (max) (mA) | 47 |
| Power factor | 0.5 |
| Lamp power (min) (W) | 4.9 |
| Lamp power (max) (W) | 4.9 |
| Voltage type | AC |
| Energy Efficiency Index (EEI) | 0.146 |
| Total harmonic distortion | 135 |