

## 8.2W 15000h BX

Replace linear halogen lamps with LEDs!

Replacement LED lamps for old linear halogen lamps. Available in two different sizes and one dimmable model. LED-linear lamps with R7s base are suitable for use as light sources in various floodlights, for example. They are efficient and energy-saving lamps. Therefore, they are ideal for use in applications where powerful light is needed for long periods, such as during renovations. The products are packed in cardboard packaging.

Opal LED linear lamp 8.2W 2700K R7S 1055lm 15000h 29x78mm, cardboard packing. Supply frequency ~50/60Hz.



8.2W 15000h BX			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4714122	A7LER1	0.036	

8.2W 15000h BX  
EC001959

#### Mounting

Degree of protection (IP)	IP20
---------------------------	------

#### Structure

Colour	Other
Housing colour	White
Energy efficiency class	E

#### Dimming and control

Dimmable	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

#### Photometric data

Luminous flux (min) (lm)	1055
Luminous flux (max) (lm)	1055
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	2700
Colour temperature (max) (K)	2700
Beam angle (min) (°)	330
Beam angle (max) (°)	330
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG0

#### Lifetime and capacity

#### Measurements

Diameter (mm)	29
Length (mm)	78

#### Electrotechnical data

Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	57
Nominal current (max) (mA)	57
Power factor	0.5
Lamp power (min) (W)	8.2
Lamp power (max) (W)	8.2
Voltage type	AC