


15.5W 15000h BX

Replace linear halogen lamps with LEDs!

Replacement LED lamps for old linear halogen lamps. Available in two different sizes and one dimmable model. LED-linear lamps with R7s base are suitable for use as light sources in various floodlights, for example. They are efficient and energy-saving lamps. Therefore, they are ideal for use in applications where powerful light is needed for long periods, such as during renovations. The products are packed in cardboard packaging.

Opal LED linear dimmable lamp 15.5W 2700K R7S
2000lm 15000h 29x118mm, cardboard packing. Supply frequency ~50/60Hz.



15.5W 15000h BX			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4714124	A7LER3	0.056	

15.5W 15000h BX
EC001959

Mounting

Degree of protection (IP)	IP20
---------------------------	------

Structure

Colour	Other
Housing colour	White
Energy efficiency class	E

Dimming and control

Dimmable	Yes
Dimming trailing edge	Yes
Dimming leading edge	Yes
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	No
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data

Luminous flux (min) (lm)	2000
Luminous flux (max) (lm)	2000
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	2700
Colour temperature (max) (K)	2700
Beam angle (min) (°)	330
Beam angle (max) (°)	330
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG0

Lifetime and capacity

Measurements

Diameter (mm)	29
Length (mm)	118

Electrotechnical data

Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Power factor	0.5
Lamp power (min) (W)	15.5
Lamp power (max) (W)	15.5
Voltage type	AC
Energy Efficiency Index (EEI)	0.11