

SmartHome

4.9W Spiral filament 15000h BX

Use Airam SmartHome lights to decorate your home with light! The stunning and eye-catching SmartHome decorative lamps do not need to be covered up with shades. The collection features lamps with both traditional bright bulbs and tinted antique bulbs. Get the most out of your luminaires with Airam SmartHome application. The lamps can also be switched on and off with a regular lighting switch, in which case the latest lighting setting will be saved in the lamp's memory. Control your Airam SmartHome products with the SmartHome application. Download the application from the App Store or Google Play Store. The application is available in Finnish, Swedish and English. Connect your devices to your home WiFi. You do not need a separate base station! Control your products with Google Assistant's, Amazon Alexa's or Siri Shortcut's voice control function.

SmartHome clear globe CCT WiFi filament LED lamp
4.9W 1800-3000K E27 380lm 15000h 165x260mm,
colour Amber, cardboard packing. Supply frequency
~50/60Hz.



4.9W Spiral filament 15000h BX

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
9410776	A7GAML	0.243	SmartHome

4.9W Spiral filament 15000h BX

EC001959

Mounting

Degree of protection (IP)	Other
---------------------------	-------

Structure

Colour	Amber
Housing colour	Colourless

Dimming and control

Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	Yes
No dimming function	No
Remote operation possible	Yes
With movement sensor	No
With remote control	Yes
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	Yes
Compatible with Amazon Alexa	Yes
IFTTT support available	No

Photometric data

Luminous flux (min) (lm)	380
Luminous flux (max) (lm)	380
Colour rendering index CRI	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	1800
Colour temperature (max) (K)	3000
Beam angle (min)	320
Beam angle (max)	320
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

Lifetime and capacity

Measurements

Diameter (mm)	165
Length (mm)	260

Electrotechnical data

Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	44
Nominal current (max) (mA)	44
Power factor	0.5
Voltage type	AC
Energy Efficiency Index (EEI)	0.137
Total harmonic distortion	135