

IP20

Airam Led

1.4W 15000h

Replace all the lamps in your home at once! Excellent value-for-money lamps are available in convenient multipacks. All Airam LED lamps come with a three-year warranty with proof of purchase.

Opal candle LED lamp 1.4W 2700K E14 136lm 15000h 35x97mm, full glass, 2 pcs in cardboard packing. Supply frequency ~50/60Hz.

1.4W 15000h

| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
|--------------|--------|------|----------------|
| 9410781 | A7GAMT | 0.02 | Airam Led |



1.4W 15000h

EC001959

Mounting

| | |
|---------------------------|------|
| Degree of protection (IP) | IP20 |
|---------------------------|------|

Structure

| | |
|----------------|-------|
| Colour | White |
| Housing colour | White |

Dimming and control

| | |
|----------------------------------|-----|
| Dimmable | No |
| Dimming trailing edge | No |
| Dimming leading edge | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming Bluetooth | No |
| Dimming Wi-Fi | No |
| No dimming function | Yes |
| Remote operation possible | No |
| With movement sensor | No |
| With remote control | No |
| With twilight switch | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

Photometric data

| | |
|----------------------------------------------|--------------|
| Luminous flux (min) (lm) | 136 |
| Luminous flux (max) (lm) | 136 |
| Colour rendering index (CRI/Ra) | 80-89 |
| Colour of light acc. EN 12464-1 | Warm <3300 K |
| Colour temperature (min) (K) | 2700 |
| Colour temperature (max) (K) | 2700 |
| Beam angle (min) (°) | 360 |
| Beam angle (max) (°) | 360 |
| Colour consistency (McAdam ellipse) | SDCM6 |
| Photobiological safety according to EN 62471 | RG1 |

Lifetime and capacity

Measurements

| | |
|---------------|----|
| Diameter (mm) | 35 |
| Length (mm) | 97 |

Electrotechnical data

| | |
|-------------------------------|-------|
| Nominal voltage (min) (V) | 220 |
| Nominal voltage (max) (V) | 240 |
| Nominal current (min) (mA) | 12 |
| Nominal current (max) (mA) | 12 |
| Power factor | 0.4 |
| Lamp power (min) (W) | 1.4 |
| Lamp power (max) (W) | 1.4 |
| Voltage type | AC |
| Energy Efficiency Index (EEI) | 0.083 |