



CABILITE

3CCT 30CM 200LM 1500MAH USB-C

Rechargeable light

Charge the versatile CabiLite light via the USB-C port. The light features a motion sensor and multiple functions, including brightness adjustment and separate night and day settings. You can adjust the light's color temperature and brightness using the button next to the charging port. A short press changes the color temperature step by step, while a long press dims the light smoothly. The lightweight and low-profile design makes it easy to attach to a cabinet, shelf, or wall – wherever you need a handy motion-sensor light! Includes a mounting plate with a magnetic attachment. Available in two lengths: 30 cm and 40 cm.



3CCT 30CM 200LM 1500MAH USB-C			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
9471198		0.13	CABILITE

Mounting	
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	No
Suitable for recessed mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Suitable for clamp-mounting	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	Other
Suitable for emergency lighting	No

Structure	
With mounting material	Yes
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Aluminium
Housing colour	Aluminium
Cover material	Plastic, opal
Exchangeable control gear	No
Emergency power supply integrated	No

Dimming and control	
Dimmable	Yes
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	No
With presence indicator	No
With movement sensor	Yes
Movement sensor/presence detector technology	Passive infrared
With light sensor	Yes
Bluetooth operated	No

Photometric data	
Beam angle	Extreme wide beam >80°
Effective luminous flux (lm)	200
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	6500
Colour rendering index (CRI/Ra)	70-79
Colour temperature switchable	Discrete positions
Lumen setting adjustable	Positions

Lifetime and capacity

Measurements	
Width (mm)	40
Height/depth (mm)	17
Length (mm)	300

Electrotechnical data	
Nominal voltage (min) (V)	5
Nominal voltage (max) (V)	5
Protection class according to IEC 61140	III
Luminaire efficacy (min) (lm/W)	200
Luminaire efficacy (max) (lm/W)	200
Maximum system power (W)	2.3