




# Cara

## CARA WALL LIGHT 4,5W/830 320LM WH

Cara Indoors wall luminaire 4.5W 3000K 320lm No dim; IP20; Protection cl. II; L70B50 25000h; LED not exchangeable; CRI>80; Ending; Colour wh; Cover Plastic, opal

CARA WALL LIGHT 4,5W/830 320LM WH			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
9610415	A1HICC	0.352	Cara



## CARA WALL LIGHT 4,5W/830 320LM WH

EC002892

Mounting	
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	No
Suitable for recessed mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP20
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Suitable for emergency lighting	No
Luminaire may be covered with thermally insulating material	blank
Type of wiring	Ending
Connection type	Other

Structure	
Lamp type	LED not exchangeable
With lamp	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing colour	White
Cover material	Plastic, opal
Energy efficiency class of light source according to EU regulation 2019/2015	F
Emergency power supply integrated	No

Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With movement sensor	No
With light sensor	No
Bluetooth operated	No

Photometric data	
Light sharing	Symmetric
Light outlet	Direct
Colour of light (alphanumeric)	White
Effective luminous flux (lm)	320
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Colour rendering index CRI	80-89
Colour temperature switchable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	25000

Measurements	
Height/depth (mm)	122
Outer diameter (mm)	74

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	230
Nominal voltage (max) (V)	230
Protection class according to IEC 61140	II
Suitable for lamp power (min) (W)	4.5
Suitable for lamp power (max) (W)	4.5
Maximum system power (W)	4.5
Luminaire efficacy (lm/W)	72