





## LED Strip 24V 24V IP20 4,8W/m 830 3m

## Led strip

Create stylish highlights and indirect lighting situations with led strips. Attach the led strip onto a clean surface with the 3M tape on the back. The thin and flat strip is easy to attach to small and narrow places such as beneath a cabinet or shelf, around a doorframe or behind the television! Add a stylish finishing touch with aluminium channels. The strip can be shortened every 100 mm by following separate instructions. Our selection includes led strips in white (3000 K) and bright white (4000 K). Available in different lengths. Plug & play -instalment makes sure the product is easy to set up and ready to go. Plug transformer with on/off switch.

LED Strip 24V LED-light strip 24W 4.8W/m wh 3000K 2000lm 400lm/m IP20; Protection cl. III; L70B50 15000h; LED not exchangeable; Ending

| 24V IP20 4,8W/m 830 3m |          |      |                |
|------------------------|----------|------|----------------|
| PRODUCT CODE           | CODE     | KG   | PRODUCT FAMILY |
| 9610484                | A1LSEA-3 | 0.15 | LED Strip 24V  |





## 24V IP20 4,8W/m 830 3m

EC002706

| Mounting                  |                       |
|---------------------------|-----------------------|
| Degree of protection (IP) | IP20                  |
| Mounting method           | Surface moun-<br>ting |
| Type of wiring            | Ending                |

| Structure  |                           |
|--|---------------------------|
| Lamp type  | LED not exchan-<br>geable |
| Self-adhesive  | Yes                       |
| Number of LEDs per metre   | 60                        |
| Model  | Tape                      |
| With connection set  | No                        |
| With end piece   | No                        |
| Energy efficiency class of light source according to EU regulation 2019/2015 | G                         |

| Dimming and control              |    |
|----------------------------------|----|
| IFTTT support available          | No |
| Compatible with Apple HomeKit    | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa     | No |

| Photometric data               |       |
|--------------------------------|-------|
| Luminous flux per meter (lm)   | 400   |
| Colour temperature (min) (K)   | 3000  |
| Colour rendering index CRI     | 80-89 |
| Colour of light (alphanumeric) | White |
| Radiation angle (°)            | 100   |
| Colour temperature (max) (K)   | 3000  |
| Colour temperature switchable  | No    |
| Lumen setting adjustable       | No    |
| Beam angle adjustable          | No    |

| Lifetime and capacity                |       |
|--------------------------------------|-------|
| Rated life time L70/B50 at 25 °C (h) | 15000 |

| Measurements |      |
|--------------|------|
| Length (mm)  | 3000 |
| Width (mm)   | 8    |

| Electrotechnical data                   |       |
|---|-------|
| Voltage type                            | AC/DC |
| Protection class according to IEC 61140 | III   |
| Lamp voltage (min) (V)                  | 24    |
| Lamp power per meter (W)                | 4.8   |
| Maximum system power (W)                | 14.4  |
| Lamp voltage (max) (V)                  | 24    |