



## LED Strip 24V

### 24V IP20 4,8W/m 840 2m

#### Led strip

With an LED strip, you can create stylish highlights and indirect lighting. Attach the strip directly to a clean surface using the 3M adhesive backing. The thin, low-profile strip is easy to install even in small or narrow spaces, such as under shelves or cabinets, inside display cases, around door frames, or behind a TV as ambient lighting. For a more refined look, use an aluminium profile during installation. The LED strip can be cut at 100 mm intervals following the provided instructions. Available in various lengths with white light (3000 K) or cool white light (4000 K). LED 24 V 4.8 W/m. Easy plug & play installation, ready to use immediately. Plug-in transformer with on/off switch on the cable. For indoor use.

LED Strip 24V LED-light strip 24W 4.8W/m wh 4000K 2000lm 400lm/m IP20; Protection cl. III; L70B50 15000h; LED not exchangeable; Ending



| 24V IP20 4,8W/m 840 2m |          |      |                |
|------------------------|----------|------|----------------|
| PRODUCT CODE           | CODE     | KG   | PRODUCT FAMILY |
| 9610486                | A1LSEB-2 | 0.14 | LED Strip 24V  |

24V IP20 4,8W/m 840 2m

EC002706

| Mounting                  |                  |
|---------------------------|------------------|
| Mounting method           | Surface mounting |
| Degree of protection (IP) | IP20             |
| Type of wiring            | Ending           |

| Structure                                                                    |                      |
|------------------------------------------------------------------------------|----------------------|
| Model                                                                        | Tape                 |
| Lamp type                                                                    | LED not exchangeable |
| Number of LEDs per metre                                                     | 60                   |
| Energy efficiency class of light source according to EU regulation 2019/2015 | G                    |
| With end piece                                                               | No                   |
| With connection set                                                          | No                   |
| Self-adhesive                                                                | Yes                  |

| Dimming and control              |    |
|----------------------------------|----|
| Compatible with Apple HomeKit    | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa     | No |
| IFTTT support available          | No |

| Photometric data                |       |
|---------------------------------|-------|
| Luminous flux per meter (lm)    | 400   |
| Radiation angle (°)             | 100   |
| Colour of light (alphanumeric)  | White |
| Colour temperature (min) (K)    | 4000  |
| Colour temperature (max) (K)    | 4000  |
| Colour rendering index (CRI/Ra) | 80-89 |
| Colour temperature switchable   | No    |
| Lumen setting adjustable        | No    |
| Beam angle adjustable           | No    |

| Lifetime and capacity                |       |
|--------------------------------------|-------|
| Rated life time L70/B50 at 25 °C (h) | 15000 |

| Measurements |      |
|--------------|------|
| Width (mm)   | 8    |
| Length (mm)  | 2000 |

| Electrotechnical data                   |       |
|-----------------------------------------|-------|
| Lamp power per meter (W)                | 4.8   |
| Voltage type                            | AC/DC |
| Lamp voltage (min) (V)                  | 24    |
| Lamp voltage (max) (V)                  | 24    |
| Protection class according to IEC 61140 | III   |
| Maximum system power (W)                | 9.6   |