




Stella Clip

IP20 3W/830 280lm WH

Clip-on luminaire

With the Stella Clip spotlight, you can replace a table or wall lamp either permanently or temporarily. Attach it easily to a shelf, desk edge, or bed headboard with the handy clip. The clip mount frees up desk space and allows the light to be moved as needed. The slim, minimalist design features a fixed LED light source with 280 lm brightness and a 3000 K white light. The flexible metal arm allows you to direct the light exactly where you need it.

Stella Table lamp 3W 3000K 280lm No dim; Protection cl. II; L70B50 20000h; LED not exchangeable; CRI>80; Housing Plastic; Colour wh



IP20 3W/830 280lm WH

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
9610502	A1FENH	0.422	Stella Clip

IP20 3W/830 280lm WH

EC000302

Mounting	
Type of luminaire	Other
Mounting method	Other
Suitable for wall mounting	No
Fit for workplace acc. EN 12464-1	No
Electrical connection with connector system	Yes
Structure	
Adjustable	Yes
Bendable	Yes
Adjustable height	Yes
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Plastic
Housing colour	White
With switch	Yes
With socket outlet	No
Energy efficiency class of light source according to EU regulation 2019/2015	D
Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming mains voltage modulation	No
Dimming manufacturer's proprietary system	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming potentiometer (integrated)	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming with push-button	No
Dimming Zigbee	No
No dimming function	Yes
With dimmer	No
Photometric data	
Direct-/indirect proportion separately controllabl	No
Effective luminous flux (lm)	280
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Colour rendering index (CRI/Ra)	80-89
Colour temperature switchable	No
Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	20000
Measurements	
Width (mm)	52
Height/depth (mm)	420

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Protection class according to IEC 61140	II
Suitable for lamp power (min) (W)	3
Suitable for lamp power (max) (W)	3
Maximum system power (W)	3