




HERBY

Herby Plant 10W/840 650lm

HERBY Botanical luminaire 10W 4000K 650lm No dim;
Protection cl. III; L70B50 25000h; LED not
exchangeable; Housing Plastic; Colour wh

Herby Plant 10W/840 650lm

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
9610506	A7GALG	0.5	HERBY



Mounting	
Suitable for surface mounting	Yes
Suitable for recessed mounting	No
Suitable for wall mounting	No
Suitable for suspended mounting	No
Suitable for ceiling mounting	No
Suitable for traverse mounting	No
Suitable for pedestal/floor mounting	No
Suitable for light-track mounting	No
Suitable for clamp-mounting	No
Suitable for low voltage cable system	No
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Fit for workplace acc. EN 12464-1	No
Luminaire may be covered with thermally insulating material	-

Structure	
Adjustability	Not adjustable
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Plastic
Surface protection	Plastic-coated
Housing colour	White
Surface brushed	No
Energy efficiency class of light source according to EU regulation 2019/2015	E

Dimming and control	
With movement sensor	No
With light sensor	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes

Photometric data	
Light outlet	Direct
Colour of light (alphanumeric)	Multi colour
Colour temperature (min) (K)	4000
Colour temperature (max) (K)	4000
Luminous flux (min) (lm)	650
Luminous flux (max) (lm)	650
Effective luminous flux (lm)	650

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	25000

Measurements	
Length (mm)	330
Width (mm)	100
Height/depth (mm)	395

Electrotechnical data	
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Protection class according to IEC 61140	III
Suitable for lamp power (min) (W)	10
Suitable for lamp power (max) (W)	10
Maximum system power (W)	10
Luminaire efficacy (lm/W)	67