




Iris

5W/835 240lm YEL USB

Grow light

This cute grow light with a delicate design is like a piece of jewelry. In addition to additional light that is vital to your plants, this light also brightens up your decor. Choose from two beautiful shades! The height of the light can be adjusted. The light is pushed directly into the soil. The luminosity can be adjusted in steps and the light also features a timer function. Works via USB connection. The package does not include a USB-A power adapter.

Iris Botanical luminaire 5W 3500K 240lm Dim Touch and Dim; Protection cl. III; L70B50 25000h; LED not exchangeable; CRI>80; Housing Plastic; Colour yel; Cover Plastic, opal



5W/835 240lm YEL USB

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
9610534	A7GANS	0.18	Iris

5W/835 240lm YEL USB

EC000302

Mounting	
Type of luminaire	Desk luminaire
Mounting method	Other
Suitable for wall mounting	No
Fit for workplace acc. EN 12464-1	No
Electrical connection with connector system	No
Structure	
Adjustable	No
Bendable	No
Adjustable height	Yes
Lamp type	LED not exchangeable
Suitable for number of lamps	1
Lamp holder	None
Housing material	Plastic
Housing colour	Yellow
Cover material	Plastic, opal
Exchangeable control gear	No
With switch	Yes
With socket outlet	No
Energy efficiency class of light source according to EU regulation 2019/2015	Not required
Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	Yes
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	No
With dimmer	Yes
Bluetooth operated	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
Compatible with Casambi	No
Photometric data	
Effective luminous flux (lm)	240
Photobiological safety according to EN 62471	RG0
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	3500
Colour temperature (max) (K)	3500
Colour rendering index CRI	80-89
Colour temperature switchable	No
Lumen setting adjustable	Positions
Beam angle adjustable	No
Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	25000

Measurements	
Width (mm)	110
Height/depth (mm)	710
Length (mm)	110
Electrotechnical data	
Voltage type	DC
Nominal voltage (min) (V)	5
Nominal voltage (max) (V)	5
Type of control gear	Electronic transformer
Protection class	III
Suitable for lamp power (min) (W)	5
Suitable for lamp power (max) (W)	5
Maximum system power (W)	5
Luminaire efficacy (lm/W)	48
Power factor	1