




Ivy

14W/835 650LM

14W/835 650LM			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
9610538	A7GANW	0.82	Ivy



14W/835 650LM
EC000302

Mounting	
Type of luminaire	Other
Mounting method	Stand (base)
Suitable for wall mounting	No
Fit for workplace acc. EN 12464-1	No
Electrical connection with connector system	No

Structure	
Adjustable	No
Bendable	No
Adjustable height	Yes
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Plastic
Housing colour	White
Cover material	Plastic, opal
Cover colour	White
Control gear included	Yes
Exchangeable control gear	Yes
With switch	Yes
With socket outlet	No
Containing product according to 2019/2020/EU	No
Energy efficiency class of light source according to EU regulation 2019/2015	Not required

Dimming and control	
Dimmable	Yes
No dimming function	No
With dimmer	Yes

Photometric data	
Direct-/indirect proportion separately controllabl	No
Light distributor	None
Effective luminous flux (lm)	650
Rated luminous flux according to IEC 62722-2-1 (min) (lm)	650
Rated luminous flux according to IEC 62722-2-1 (max) (lm)	650
Photobiological safety according to EN 62471	RG0
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	3500
Colour temperature (max) (K)	3500
Colour rendering index (CRI/Ra)	80-89
Colour temperature switchable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	25000

Measurements	
Width (mm)	200
Height/depth (mm)	229
Length (mm)	200

Electrotechnical data	
Voltage type	AC/DC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Type of control gear	Not required
Protection class according to IEC 61140	III
Suitable for lamp power (min) (W)	14
Suitable for lamp power (max) (W)	14
Maximum system power (W)	14
Luminaire efficacy (lm/W)	45.8