



Lucio Bollard

IP44 1W/830 BK

Lucio Bollard 3000K 90lm IP44; Protection cl. III;
L70B50 10000h; LED not exchangeable; CRI>80;
Housing st; Colour bk; Cover Plastic, opal

IP44 1W/830 BK

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
9610602		0.25	Lucio Bollard



IP44 1W/830 BK

EC000301

Mounting	
Type of luminaire	Bollard luminaire
Degree of protection (IP)	IP44
Connection type	Screwless terminal

Structure	
With base plate	No
Lamp type	LED not exchangeable
With lamp	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Stainless steel
Material quality housing material	Other
Housing colour	Black
Cover material	Plastic, opal
Energy efficiency class of light source according to EU regulation 2019/2015	G

Dimming and control	
With light sensor	No
With movement sensor	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Effective luminous flux (lm)	90
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Colour rendering index CRI	80-89
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	10000

Measurements	
Height/depth (mm)	348
Diameter (mm)	57

Electrotechnical data	
Voltage type	DC
Nominal voltage (min) (V)	9
Nominal voltage (max) (V)	15
Type of control gear	LED operating device voltage-controlled
Protection class according to IEC 61140	III
Suitable for lamp power (min) (W)	1
Suitable for lamp power (max) (W)	1
Luminaire efficacy (lm/W)	90
Power factor	1