



# Enna 220

## E27 MAX20W BL TXT DIFF


Pendant light

With its rounded design, the Enna pendant light fits various decoration styles. A diffuser below the globe softens the light for a cozy atmosphere. A bulb is not included in the package, so choose the best E27-socket option from our wide range. Also try the SmartHome LED bulbs that allow you to adjust the lighting to fit your mood! You can also take a look the larger Enna 434 light from the same range.



### E27 MAX20W BL TXT DIFF

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
9610628		0.6	Enna 220



## E27 MAX20W BL TXT DIFF

EC001743

Mounting	
Suitable for light line configuration	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP20
Suitable for emergency lighting	No
Connection type	Other
Structure	
Lamp type	LED exchangeable
Light source included	No
Suitable for number of lamps	1
Lamp holder	E27
Housing material	Steel
Housing colour	Black
Cover material	Plastic, opal
Control gear included	No
Exchangeable control gear	No
Emergency power supply integrated	No
Suspension supplied with the product	Yes
Pendant length (min) (mm)	260
Pendant length (max) (mm)	1575
Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming potentiometer (integrated)	No
Dimming programmable	No
Dimming RF	No
Dimming LineSwitch	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Bluetooth operated	No
Photometric data	
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No
Lifetime and capacity	
Measurements	
Height/depth (mm)	195
Diameter (mm)	220

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Type of control gear	Not required
Protection class according to IEC 61140	II
Suitable for lamp power (max) (W)	11