



Anile

15W 800lm LED 3K WH/CH 30cm

LED pendant light


This stunning pendant light with soft lines provides the perfect finishing touch to your decor! The interior of the shade features a lovely champagne color and a ring-like pattern that creates atmospheric shimmer in the room. Anile is beautiful both above a dining table or in the living room. The light is equipped with a fixed LED, which can be dimmed using an LED dimmer. Available in two colors.

Anile Decorative luminaire 15W 3000K 800lm IP20;
LED not exchangeable; Lamp included; CRI>80;
Housing Steel; Colour Multi colour.



15W 800lm LED 3K WH/CH 30cm

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
9610637		1.5	Anile



15W 800lm LED 3K WH/CH 30cm
EC001743

Mounting	
Suitable for light line configuration	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP20
Suitable for emergency lighting	No
Connection type	Screwed terminal

Structure	
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Steel
Housing colour	Multi colour
Control gear included	No
Exchangeable control gear	No
Emergency power supply integrated	No
Suspension supplied with the product	Yes
Pendant length (min) (mm)	260
Pendant length (max) (mm)	1400

Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming potentiometer (integrated)	No
Dimming programmable	No
Dimming RF	No
Dimming LineSwitch	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Bluetooth operated	No

Photometric data	
Colour consistency (McAdam ellipse)	SDCM6
Effective luminous flux (lm)	800
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Colour rendering index (CRI/Ra)	80-89
Colour temperature switchable	No
Lumen setting adjustable	Continuously variable
Beam angle adjustable	No

Lifetime and capacity

Measurements	
Height/depth (mm)	240
Diameter (mm)	300

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Type of control gear	Not required
Protection class according to IEC 61140	I
Maximum system power (W)	15
Luminaire efficacy (lm/W)	53