

IP20



Unna

250LM CLEAR-WHITE


Pendant light

A stylish and stunning pendant light with an E27 Unna bulb attached to a fabric-covered cord. Available with a clear Unna bulb and white cord or amber-colored bulb and black cord. The globe of the Unna bulb houses a beautiful warm white LED that reaches vertically from the top of the globe to the bottom. Globe width 191 mm, height 220 mm. Metal canopy, lighting plug included.



250LM CLEAR-WHITE

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
9610649		0.872	Unna



250LM CLEAR-WHITE

EC001743

Mounting	
Suitable for light line configuration	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP20
Suitable for emergency lighting	No
Connection type	Other
Structure	
Lamp type	LED exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	E27
Housing material	Aluminium
Housing colour	White
Energy efficiency class of light source according to EU regulation 2019/2015	G
Containing product according to 2019/2020/EU	No
Emergency power supply integrated	No
Suspension supplied with the product	Yes
Pendant length (min) (mm)	1500
Pendant length (max) (mm)	1500
Dimming and control	
Dimmable	Yes
No dimming function	No
With movement sensor	No
With presence indicator	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
Compatible with Casambi	No
IFTTT support available	No
Bluetooth operated	No
Photometric data	
Colour consistency (McAdam ellipse)	SDCM6
Direct-/indirect proportion separately controllabl	No
Rated luminous flux according to IEC 62722-2- 1 (min) (lm)	250
Rated luminous flux according to IEC 62722-2- 1 (max) (lm)	250
Effective luminous flux (lm)	250
Colour temperature (min) (K)	2700
Colour temperature (max) (K)	2700
Colour rendering index (CRI/Ra)	80-89
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No
Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	15000
Measurements	
Height/depth (mm)	220
Diameter (mm)	191

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Type of control gear	Not required
Luminaire efficacy (min) (lm/W)	63
Luminaire efficacy (max) (lm/W)	63
Suitable for lamp power (min) (W)	4
Suitable for lamp power (max) (W)	4
Maximum system power (W)	4
Luminaire efficacy (lm/W)	63