



160LM 3,3W 3000K USB-C RG

Rechargeable table lamp

Rechargeable, compact and easy-to-use table lamp. Create a moody atmosphere for your home with this lamp. Emits white light (3000 K), which can be dimmed steplessly by pressing and holding the on/off touch switch. The frame comes in three different colors: black, white and rose gold. USB-C charging port on the stand. Charging cable is included, but a power adapter is not. Size with the charging stand: Ø 11 cm, height 30.5 cm.

160LM 3,3W 3000K USB-C RG

| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
|--------------|------|------|----------------|
| 9610700 | | 0.75 | |



| Mounting | |
|--|-----------------------|
| Type of luminaire | Desk luminaire |
| Mounting method | Stand (base) |
| Suitable for wall mounting | No |
| Fit for workplace acc. EN 12464-1 | No |
| Electrical connection with connector system | No |
| Structure | |
| Adjustable | No |
| Bendable | No |
| Adjustable height | No |
| Lamp type | LED not exchangeable |
| Light source included | Yes |
| Suitable for number of lamps | 1 |
| Lamp holder | Other |
| Housing material | Steel |
| Housing colour | Gold |
| Cover material | Plastic, opal |
| With switch | Yes |
| With socket outlet | No |
| Energy efficiency class of light source according to EU regulation 2019/2015 | G |
| Dimming and control | |
| Dimmable | Yes |
| Dimming Touch and Dim | Yes |
| No dimming function | No |
| With dimmer | Yes |
| Bluetooth operated | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| Compatible with Casambi | No |
| IFTTT support available | No |
| Photometric data | |
| Effective luminous flux (lm) | 160 |
| Colour temperature (min) (K) | 3000 |
| Colour temperature (max) (K) | 3000 |
| Colour rendering index (CRI/Ra) | 80-89 |
| Colour consistency (McAdam ellipse) | SDCM6 |
| Colour temperature switchable | No |
| Lumen setting adjustable | Continuously variable |
| Lifetime and capacity | |
| Measurements | |
| Height/depth (mm) | 305 |
| Diameter (mm) | 111 |
| Electrotechnical data | |
| Voltage type | DC |
| Nominal voltage (min) (V) | 5 |
| Nominal voltage (max) (V) | 5 |
| Protection class according to IEC 61140 | III |
| Suitable for lamp power (min) (W) | 3 |
| Suitable for lamp power (max) (W) | 3.3 |
| Maximum system power (W) | 3.3 |
| Luminaire efficacy (lm/W) | 48 |