




## 10W 950 600lm 3CCT DIM

10W 950 600lm 3CCT DIM

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
9610701		1.26	



Mounting	
Type of luminaire	Desk luminaire
Mounting method	Stand (base)
Suitable for wall mounting	No
Fit for workplace acc. EN 12464-1	Yes

Structure	
Adjustable	Yes
Bendable	No
Adjustable height	Yes
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Aluminium
Housing colour	White
Cover material	Other
Cover colour	Aluminium
Exchangeable control gear	No
With switch	Yes
With socket outlet	No
Containing product according to 2019/2020/EU	Yes
Energy efficiency class of light source according to EU regulation 2019/2015	G

Dimming and control	
Dimmable	Yes
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming mains voltage modulation	No
Dimming manufacturer's proprietary system	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming potentiometer (integrated)	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming with push-button	No
Dimming Zigbee	No
No dimming function	No
With dimmer	Yes
Constant luminous flux control	No
Bluetooth operated	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
Compatible with Casambi	No
IFTTT support available	No

Photometric data	
Direct-/indirect proportion separately controllabl	Yes
Light distributor	None
Effective luminous flux (lm)	600
Rated luminous flux according to IEC 62722-2-1 (max) (lm)	835
Photobiological safety according to EN 62471	RG0
Colour of light (alphanumeric)	Multi colour
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	6500
Colour rendering index (CRI/Ra)	90-100
Colour consistency (McAdam ellipse)	SDCM5
Colour temperature switchable	Discrete positions
Lumen setting adjustable	Positions

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	25000

Measurements	
Width (mm)	255
Height/depth (mm)	480
Length (mm)	440

Electrotechnical data	
Voltage type	AC/DC
Nominal voltage (min) (V)	12
Nominal voltage (max) (V)	220
Type of control gear	LED operating device voltage-controlled
Protection class according to IEC 61140	III
Suitable for lamp power (min) (W)	0.5
Suitable for lamp power (max) (W)	10
Maximum system power (W)	10
Luminaire efficacy (lm/W)	60
Power factor	0.5