



# LOFT


## LOFT35 PENDANT LIGHT E27 BK

Pendant luminaire

The industrial-style Loft pendant is ideal as general lighting for dining areas, kitchens, living rooms, or bedrooms. By adjusting the installation height of the shade, you can determine how widely the light spreads. The shade and ceiling cup have a matte metal finish in painter's white or dark grey. The textile-covered cord comes with a lamp plug. Try different bulbs and LED light sources – E27-base bulb sold separately.

LOFT Decorative luminaire IP20; Protection cl. II; LED exchangeable; Housing Steel; Colour bk

LOFT35 PENDANT LIGHT E27 BK			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
9783081		1.16	LOFT



## LOFT35 PENDANT LIGHT E27 BK

EC001743

Mounting	
Suitable for light line configuration	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP20
Suitable for emergency lighting	No
Connection type	Other
Structure	
Lamp type	LED exchangeable
Light source included	No
Suitable for number of lamps	1
Lamp holder	E27
Housing material	Steel
Housing colour	Black
Energy efficiency class of light source according to EU regulation 2019/2015	Not required
Emergency power supply integrated	No
Suspension supplied with the product	Yes
Pendant length (min) (mm)	500
Pendant length (max) (mm)	1500
Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming potentiometer (integrated)	No
Dimming programmable	No
Dimming RF	No
Dimming LineSwitch	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Bluetooth operated	No
Photometric data	
Direct-/indirect proportion separately controllabl	No
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No
Lifetime and capacity	
Measurements	
Width (mm)	350
Height/depth (mm)	215
Length (mm)	350
Diameter (mm)	350

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Protection class according to IEC 61140	II
Suitable for lamp power (min) (W)	1
Suitable for lamp power (max) (W)	60