





Plata

IP20 26W/830 EU PSMP WH

Plata is a low-profile modular luminaire designed for offices, corridors, lobbies, schools and other public spaces. Anti-glare models equipped with micro-prismatic (MP) diffusers offer an excellent solution for classrooms and spaces where computers and other equipment with displays are used. Plata is suitable for recessed mounting in false ceilings, which makes it ideal for offices and public spaces. It can also be suspended on wires or surface-mounted with a separate mounting set. The control options are on/off, Dali-2, pushbutton (direct pushbutton control 230V) and Casambi.

Plata Modular luminaire 26W 3000K 2800lm No dim; IP20; IK02; Protection cl. II; L70B50 100000h; LED not exchangeable; Lamp included; CRI>80; SDCM3; Ending; 2x0.75mm²; Housing al; Colour wh; Cover Plastic, structured; C16 max. 74



IP20 26W/830 EU PSMP WH

| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
|--------------|-----------|------|----------------|
| A1UPAI-EU | A1UPAI-EU | 3 kg | Plata |

| Mounting | |
|--|--------|
| Suitable for wall mounting | No |
| Suitable for suspended mounting | Yes |
| Suitable for ceiling mounting | Yes |
| Suitable for recessed mounting | Yes |
| Suitable for surface mounting | Yes |
| Suitable for light line configuration | No |
| Fit for workplace acc. EN 12464-1 | Yes |
| Max. number of luminaires per miniature circuit breaker B16 | 44 |
| Max. number of luminaires per miniature circuit breaker C16 | 74 |
| Degree of protection (IP) | IP20 |
| Impact strength | IK02 |
| Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24 | Yes |
| Suitable for emergency lighting | No |
| Luminaire may be covered with thermally insulating material | No |
| Type of wiring | Ending |
| Number of poles | 2 |
| Conductor cross section (mm ²) | 0.75 |
| Connection type | Plug |
| Quantity of luminaires for MCB C16: | 74 |
| Quantity of luminaires for MCB B16: | 44 |

| Structure | |
|--|----------------------|
| Lamp type | LED not exchangeable |
| With lamp | Yes |
| Suitable for number of lamps | 1 |
| Lamp holder | Other |
| Housing material | Aluminium |
| Housing surface protection | Powder coating |
| Housing colour | White |
| Cover material | Plastic, structured |
| Type of grid | None |
| Control gear included | Yes |
| Exchangeable control gear | Yes |
| Energy efficiency class of light source according to EU regulation 2019/2015 | Not required |
| Emergency power supply integrated | No |
| With air slots | No |
| Filament test according to IEC 60695-2-11 | 650 °C - 30 s |

| Dimming and control | |
|---|-----|
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI-2 | No |
| Dimming DALI | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming potentiometer (integrated) | No |
| Dimming LineSwitch | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming phase cut-off | No |
| Dimming phase cut-on | No |
| Dimming programmable | No |
| Dimming RF | No |
| Dimming Sine Wave Reduction | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| No dimming function | Yes |
| With movement sensor | No |
| With light sensor | No |
| Constant luminous flux control | No |
| Bluetooth operated | No |
| Compatible with Casambi | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

| Photometric data | |
|--|---------------------------|
| Light distributor | Diffuser lens/optic/panel |
| Light sharing | Symmetric |
| Beam angle | Open beam |
| Colour consistency (McAdam ellipse) | SDCM3 |
| Light outlet | Direct |
| Effective luminous flux (lm) | 2800 |
| Colour of light (alphanumeric) | White |
| Colour temperature (min) (K) | 3000 |
| Colour temperature (max) (K) | 3000 |
| Flickering value Pst LM | 1 |
| Colour rendering index CRI | 80-89 |
| Stroboscope effect value SVM | 0.4 |
| Photobiological safety according to EN 62471 | RG0 |
| Unified Glare Rating (UGR) | 19 |
| Colour temperature switchable | No |
| Lumen setting adjustable | No |
| Beam angle adjustable | No |

| Lifetime and capacity | |
|---|--------|
| Rated life time L70/B50 at 25 °C (h) | 100000 |
| Lumen maintenance at median useful life of 35,000 hrs at 25 °C ambient (tq) | 90 |
| Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) | 85 |
| Failure rate at median useful life of 35,000 hrs at 25 °C ambient (tq) | 5 |
| Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) | 5 |
| Rated ambient temperature acc. IEC62722-2-1 (min) (°C) | 0 |
| Rated ambient temperature acc. IEC62722-2-1 (max) (°C) | 25 |

| Measurements | |
|----------------------------|-----|
| Width (mm) | 595 |
| Height/depth (mm) | 8.5 |
| Length (mm) | 595 |
| Built-in length (mm) | 600 |
| Built-in width (mm) | 600 |
| Built-in height/depth (mm) | 80 |

| Electrotechnical data | |
|-----------------------------------|---|
| Voltage type | AC |
| Nominal voltage (min) (V) | 220 |
| Nominal voltage (max) (V) | 240 |
| Nominal current (min) (mA) | 700 |
| Nominal current (max) (mA) | 700 |
| Type of control gear | LED operating device current-controlled |
| Protection class | II |
| Suitable for lamp power (min) (W) | 26 |
| Suitable for lamp power (max) (W) | 26 |
| Maximum system power (W) | 26 |
| Luminaire efficacy (lm/W) | 108 |
| Power factor | 0.9 |
| Total harmonic distortion | 20 |